

North Queensland Bulk Ports Corporation Mky

Southern and Northern Stations

Ambient Air Quality Monitoring

Validated Report

1st April – 30th April 2022

Report No.: DAT18388

Report issue date: 27th May 2022

Maintenance contract: MC950

Acoem Australasia (Ecotech Pty Ltd) ABN: 32005752081 1492 Ferntree Gully Rd, Knoxfield VIC. 3180. AUSTRALIA Tel No: +61397307800 Fax No: 1300 668 763

Email info.au@acoem.com WEB acoem.com.au

This document shall not be reproduced except for in full, without the written approval of Acoem Australasia

North Queensland Bulk Ports Corporation

Customer Details	;
Customer	North Queensland Bulk Ports Corporation
Contact name	Luke Galea
Address	Level 1, Waterfront Place, Mulherin Drive, Mackay Harbour, Mackay Harbour QLD 4740
Email	lgalea@nqbp.com.au
Phone	0439 782 436

Revision History					
Revision	Analyst				
0	DAT18388	27/05/2022	Anand Shrivastava		

Report by: A

Anand Shrivastava

Ster.

Signatory:

Jon Alexander

a

North Queensland Bulk Ports Corporation

Talal				
lap	le c	DT C	ont	ents

Customer Details2
Revision History2
Table of Contents
List of Figures4
List of Tables5
Executive Summary
1.0 Introduction7
2.0 Monitoring and Data Collection7
2.1. Siting Details7
2.2. Monitored Parameters9
2.3. Data Collection Methods9
2.3.1. Data Acquisition9
2.4. Data Validation and Reporting10
2.4.1. Validation10
2.4.2. Reporting10
2.5. Calibrations and Maintenance11
2.5.1. Units and Uncertainties11
2.5.2. Maintenance
2.5.2.1. Calibration & Maintenance Summary Tables11
3.0 Results
3.1. Data Capture
3.2. Air Quality Summary13

North Queensland Bulk Ports Corporation

3	.2.1.	Air Quality Categories1	4
3.3.	Tab	ulated Data1	17
3.4.	Gra	phic Representations1	8
4.0	Valid [Data Exception Tables	21
5.0	Report	t Summary2	22
Appen	dix 1 - [Definitions & Abbreviations2	23
Appen	dix 2 - E	Explanation of Exception Table	24

List of Figures

Figure 1: Southern and Northern Monitoring Stations Location	8
Figure 2: Hourly PM_{10} Averages for NQBP Mky Southern Station Assessed Against the Air Quality Category	15
Figure 3: Hourly PM_{10} Averages for NQBP Mky Northern Station Assessed Against the Air Quality Category	16
Figure 4: Southern station PM ₁₀ 24 Hour Averages April 2022	18
Figure 5: Northern station PM ₁₀ 24 Hour Averages April 2022	19
Figure 6: Southern and Northern Stations PM ₁₀ 24 Hour Averages Comparison April 2022	20

North Queensland Bulk Ports Corporation

List of Tables

Table 1: Southern and Northern Stations Siting	7
Table 2: Parameters Measured at the Southern and Northern Monitoring Stations	9
Table 3: Methods	9
Table 4: Units and Uncertainties	. 11
Table 5: Southern and Northern Stations Maintenance Table April 2022	. 12
Table 6: Monthly Data Capture for Southern and Northern stations for April 2022	. 13
Table 7: General statistics for April 2022	13
Table 8: Colour-coded categories for Air Quality Category	. 14
Table 9: Southern and Northern Stations Data Table April 2022	. 17
Table 10: Southern Station PM_{10} Valid Data Exception Table	21
Table 11: Northern Station PM $_{10}$ Valid Data Exception Table	21

North Queensland Bulk Ports Corporation

Executive Summary

North Queensland Bulk Ports Corporation has commissioned Acoem Australasia to conduct air quality monitoring for the Mackay Dust Monitoring Program. The monitoring stations at Southern and Northern sites are each equipped with an E-Sampler. Both E-samplers were equipped to measure TSP until 12th June 2020 when the E-Sampler heads at both stations were changed to measuring PM₁₀.

The air quality stations were commissioned in July 2016.

This report presents the data collected from the Southern and Northern stations during the month of April 2022.

Data capture for Northern station was 99.9% and Southern station was 99.9% for April 2022.

The PM₁₀ monthly average for Southern station was 17 μ g/m³ with a standard deviation of 9 μ g/m³.

The PM₁₀ monthly average for Northern station was 26 μ g/m³ with a standard deviation of 15 μ g/m³.

North Queensland Bulk Ports Corporation

1.0 Introduction

Acoem Australasia was commissioned by North Queensland Bulk Ports Corporation to provide monitoring and data reporting for the Mackay Dust Monitoring Program at Southern and Northern monitoring stations, located in Mackay Harbour, QLD, Australia as detailed in Table 1.

Acoem Australasia commenced data collection from both stations on 20th July 2016.

This report presents the data for the $1^{st} - 30^{th}$ April 2022

The data presented in this report:

- Describes air quality measurements;
- Compares monitoring results;
- Has been quality assured.

2.0 Monitoring and Data Collection

2.1. Siting Details

Station locations and siting details are described below.

Site Name	Geographical Coordinates	Height Above Sea Level (m)	
Northern	21° 06' 4.18" S 149°13'26.10" E	5m	
Southern	21° 06' 22.3" S 149°13'28.4" E	5m	

Table 1: Southern and Northern Stations Siting

North Queensland Bulk Ports Corporation



Figure 1: Southern and Northern Monitoring Stations Location

North Queensland Bulk Ports Corporation

2.2. Monitored Parameters

Table 2 below details the parameters monitored and the instruments used at the Southern and Northern stations. Appendix 1 defines any abbreviated parameter names used throughout the report.

Table 2: Parameters Measured at the Southern and Northern Monitoring Stations

Parameter Measured	Instrument and Measurement Technique
PM ₁₀	Met One E-Sampler – light scatter aerosol monitor

2.3. Data Collection Methods

Table 3 shows the methods used for data collection.

Table 3: Methods

Parameter Measured	Data Collection Methods Used	Description of Method
PM ₁₀ (E- Sampler)	Met One E-Sampler Operation Manual	Met One E-Sampler Operation Manual

2.3.1. Data Acquisition

Data is logged by the E-sampler at each monitoring site. Each E-sampler is equipped with a 4G modem for remote data collection. The recorded data is remotely collected from the E-samplers on a daily basis (using Airodis[™] version 5.1.5) and stored at Acoem Australasia's Environmental Reporting Services (ERS) department in Melbourne, Australia. Data samples are logged in 5-minute intervals.

North Queensland Bulk Ports Corporation

2.4. Data Validation and Reporting

2.4.1. Validation

The Acoem Australasia ERS department performs daily data checks to ensure maximum data capture rates are maintained. Any equipment failures are communicated to the responsible field engineers for urgent rectification. Acoem Australasia ERS maintains two distinct databases containing non-validated and validated data respectively.

The validated database is created by duplicating the non-validated database and then flagging data affected by instrument faults, calibrations and other maintenance activities. The data validation software requires the analyst to supply a valid reason (e.g., backed by maintenance notes, calibration sheets etc) in the database for flagging any data as invalid.

Validation is performed by the Acoem Australasia ERS operator, and the validation is reviewed. All data is checked and graphs and reports are generated based on the verified five-minute data.

2.4.2. Reporting

The reported data is in a Microsoft Excel format file named "NQBP Mky Southern and Northern Stations Data Report April 2022.xlsx".

The Excel file consists of six worksheets:

- 1. Cover
- 2. 5 Minute Data Averages
- 3. 15 Minute Data Averages
- 4. 1 Hour Data Averages
- 5. 24 Hour Data Averages
- 6. Valid Data Exception Tables

The data contained in these reports is based on Australian Eastern Standard Time. Data is for all parameters measured continuously.

All averages are calculated from the five-minute data. Averages are based on a minimum of 75% valid readings within the averaging period. Averaging periods of eight hours or less are reported for the end of the period, i.e., the hourly average 02:00am is for the data collected from 1:00am to 2:00am. One-hour averages are calculated based on a clock hour. One day and one-year averages are calculated based on calendar days.

North Queensland Bulk Ports Corporation

2.5. Calibrations and Maintenance

2.5.1. Units and Uncertainties

The uncertainties for each parameter have been determined by the manufacturer's tolerance limits of the equipment's parameters, and by the data collection standard method.

The reported uncertainties are expanded uncertainties, calculated using coverage factors which give a level of confidence of approximately 95%.

Parameter	Units	Resolution	Uncertainty ¹	Measurement Range
PM ₁₀ (E-Sampler)	μg/m³	1 μg/m³	± 10% to gravimetric method ²	0 to 65 mg/m ³

Table 4: Units and Uncertainties

2.5.2. Maintenance

Scheduled maintenance is completed every 2 months by Acoem Australasia.

2.5.2.1. Calibration & Maintenance Summary Tables

The last calibrations for the following parameters were performed on the indicated dates. Data supplied after this time is subject to verification, to be performed at the next calibration cycle.

Note: Maintenance and calibration dates may differ, as calibrations may be less frequent than scheduled maintenance visits.

Table 5 indicates when the particulate equipment was last maintained/calibrated.

¹ Uncertainties are calculated based on the full measurement range unless stated otherwise

² Manufacturer's stated accuracy for nephelometer when calibrated for local particulate type.

North Queensland Bulk Ports Corporation

Table 5: Southern and Northern Stations Maintenance Table April 2022

Station	Parameter	Date of Last Maintenance	Maintenance Type	Date of Last Calibration
Southern	PM ₁₀	04/04/2022	2-monthly	04/04/2022
Northern	PM ₁₀	04/04/2022	2-monthly	04/04/2022

3.0 Results

3.1. Data Capture

Data capture is calculated from 5-minute data, and refers to the amount of available data collected during the report period.

The percentage of data captured is calculated using the following equation:

Data capture = (Reported air quality data / Total data) x 100%

Where:

- Reported air quality data = Number of instrument readings which have been verified through a quality assured process and excludes all data errors, zero data collection due to calibration, failures and planned and unplanned maintenance.
- Total data = Total number of samples (instrument readings) expected for the sampling period. Total data is calculated based on the same averaging period as "reported air quality data" and the duration of the corresponding report period. e.g., for 5-minute data collected over a month of 31 days, the total data would be equal to 12 (5-minute samples in an hour) x 24 (hours in a day) x 31 (days in a month) = 8928 samples.

North Queensland Bulk Ports Corporation

Table 6 below displays data capture statistics for April 2022. **Bold** values in the table indicate data capture below 95%.

Table 6: Monthly Data Capture for Southern and Northern stations for April 2022

Station	Parameter	Data Capture (%)
Southern	PM10	99.9
Northern	PM ₁₀	99.9

3.2. Air Quality Summary

Table 7 below presents some statistical parameters for April 2022. The standard deviation is calculated based on the 5-minute averaged data.

Table 7: General statistics for April 2022

Station	Parameter	Time Period	Average (μg/m³)	Standard Deviation (µg/m³)
Southern	PM ₁₀	1 month	17	9
Northern	PM ₁₀	1 month	26	15

North Queensland Bulk Ports Corporation

3.2.1. Air Quality Categories

Air quality categories rather than an air quality index have been adopted to align with a Nationally consistent method of reporting of air quality data.

Each air quality measurement from a monitoring station is assigned an air quality category rating based on comparison of the measurement value against the relevant air quality guideline. Five colour-coded air quality categories are used, being 'Good' (green), 'Fair' (yellow), 'Poor' (orange), 'Very Poor' (red) or 'Extremely Poor' (dark red). Values greater than the air quality guideline will be appear as 'Poor', 'Very Poor' or 'Extremely Poor'.⁴

The Air Quality Categories rating is based on 1-hour averages values.

Table 8: Colour-coded Categories for Air Quality Categories

Not	Good	Fair	Poor	Very poor	Extremely poor	
available	<50	50-100	100.1-200	200.1-600	>600	

The PM_{10} 1-hour average values for the reporting month at the Northern and Southern stations were assessed against the air quality category rating, and the pie chart on the next pages presents the percentage of the time for which a specific air quality category was identified.

North Queensland Bulk Ports Corporation




Figure 2: Hourly PM₁₀ Averages for NQBP Mky Southern Station Assessed Against the Air Quality Category

84.2% of time during the reporting period presented by the Air Quality Category are classified as Good and 15.8% of time are classified as Fair. 0.0% of time are classified as Poor, Very Poor, Extremely Poor and Not available.

North Queensland Bulk Ports Corporation




Figure 3: Hourly PM₁₀ averages for NQBP Mky Northern Station Assessed Against the Air Quality Category

55.7% of time during the reporting period presented by the Air Quality Category are classified as Good and 38.8% of time are classified as Fair. 5.4% of time are classified as Poor, 0.1% of time are classified as Very Poor, 0.0% of time are classified as Extremely Poor and Not available.

North Queensland Bulk Ports Corporation

3.3. Tabulated Data

Table 9 details the daily averages for PM_{10} measured at Southern and Northern stations during April 2022.

Date	Southern	Northern
	(µg/m³)	(μg/m³)
1-04-2022	13	16
2-04-2022	14	21
3-04-2022	11	17
4-04-2022	10	15
5-04-2022	13	19
6-04-2022	16	24
7-04-2022	17	29
8-04-2022	23	35
9-04-2022	23	34
10-04-2022	8	10
11-04-2022	13	22
12-04-2022	12	32
13-04-2022	12	31
14-04-2022	14	20
15-04-2022	14	20
16-04-2022	13	19
17-04-2022	10	17
18-04-2022	10	15
19-04-2022	8	12
20-04-2022	9	10
21-04-2022	13	20
22-04-2022	18	33
23-04-2022	28	41
24-04-2022	27	39
25-04-2022	30	45
26-04-2022	34	58
27-04-2022	23	33
28-04-2022	20	29
29-04-2022	22	32
30-04-2022	20	29

Table 9: Southern and Northern Stations Data Table April 2022

North Queensland Bulk Ports Corporation

3.4. Graphic Representations

Validated PM₁₀ data was used to construct the following monthly graphic representations.




Figure 4: Southern station PM₁₀ 24 Hour Averages April 2022

North Queensland Bulk Ports Corporation




Figure 5: Northern station PM₁₀ 24 Hour Averages April 2022

North Queensland Bulk Ports Corporation




Figure 6: Southern and Northern Stations PM₁₀ 24 Hour Averages Comparison April 2022

North Queensland Bulk Ports Corporation

4.0 Valid Data Exception Tables

The tables below detail all changes made to the raw data set during the validation process. An explanation of reasons given in the table can be found in Appendix 2.

Table 10: Southern Station PM₁₀ Valid Data Exception Table

Start Date	End Date	Reason	Change Details	User Name	Change Date
04-04-22 09:45	04-04-22 10:05	Scheduled 2-monthly maintenance	PM10	AS	27-05-22

Table 11: Northern Station PM₁₀ Valid Data Exception Table

Start Date	End Date	Reason	Change Details	User Name	Change Date
04-04-22 10:55	04-04-22 11:20	Scheduled 2-monthly maintenance	PM ₁₀	AS	27-05-22

North Queensland Bulk Ports Corporation

5.0 Report Summary

- Data capture for Northern station was 99.9% and Southern station was 99.9% for April 2022.
- The PM₁₀ monthly average for Southern station was 17 μ g/m³ with a standard deviation of 9 μ g/m³.
- The PM₁₀ monthly average for Northern station was 26 μ g/m³ with a standard deviation of 15 μ g/m³.

-----END OF REPORT-----

North Queensland Bulk Ports Corporation

Appendix 1 - Definitions & Abbreviations

µg/m³	Micrograms per cubic metre at standard temperature and pressure (0°C and 101.3
μg/111	kPa)

PM₁₀ Particulates less than 10 microns equivalent in aerodynamic diameter

North Queensland Bulk Ports Corporation

Appendix 2 - Explanation of Exception Table

Commissioning refers to the initial setup and calibration of the instrument when it is first installed. For some instruments there may be a stabilisation period before normal operation commences.

Data transmission error refers to a period of time when the instrument could not transmit data. This may be due to interference, or a problem with the phone line or modem.

Equipment malfunction/instrument fault refers to a period of time when the instrument was not in the normal operating mode and did not measure a representative value of the existing conditions.

Gap in data/data not available refers to a period of time when either data has been lost or could not be collected.

Instrument Alarm refers to an alarm produced by the instrument. A range of alarms can be produced depending on how operation of the instrument is being affected.

Instrument out of service refers to a lack of data due to an instrument being shut down for repair, maintenance, or factory calibration.

Linear offset or multiplier refers to when an offset or multiplier has been applied between two points where the values of the offset or multiplier are different and the correction is interpolated between the two points.

Logger error refers to when an error occurs and instrument readings are not correctly recorded by the logger.

Maintenance refers to a period of time when the logger/instrument was switched off due to maintenance.

Power Interruption refers to no power to the station therefore no data was collected at this time.

Stabilisation following power interruption refers to the startup period of an instrument after power has been restored.